

PAPER HANDLING CAPABILITY

STOCK WEIGHTS

MAX 250 gsm

MIN 50 gsm

PAPER SIZES

MAX 520 mm x 350 mm
20" x 13 3/4"

MIN 200 mm x 115 mm
8" x 4 1/2"

SETS PER HOUR

WITH THE BDF OR SMB4

Up to 4.200 sets/hour

ELECTRICAL RATINGS

POWER REQUIRED 120/230 VAC
50/60 Hz

POWER CONSUMPTION 1600 W max

RADIANT HEAT

MAX 5.460 BTU/h

STANDBY 460 BTU/h

NOISE LEVEL

65 dBA (single tower without attachments)

DIMENSIONS

LENGTH BST-d main:
930 mm or 36 3/4"

BST-d additional:
910 mm or 36"

WIDTH 730 mm or 29"

HEIGHT 2000 mm or 79"

WEIGHT BST-d main:
358 kg or 788 lbs

BST-d additional:
360 kg or 790 lbs

Production rates subject to environmental conditions, operator ability and quality of stock.
As a consequence of our policy of continuous improvement, specifications are subject to change without notice.

9133620 ind A - April 2004

 **c.p. bourg**



www.cpbourg.com

Bourg is a registered trademark of C.P. Bourg, Inc. and C.P. Bourg S.A. Patents pending.

C.P. Bourg S.A. N.V.
rue des Technologies 22
B-1340 Ottignies - Belgium
Tel. : +32 10 62 22 11

Export fax : +32 10 61 63 55
Email : contactus@cpbourg.com
export.be@cpbourg.com

C.P.Bourg Inc
50 Samuel Barnet Blvd.
New Bedford, MA 02745
USA

Tel. : +1 508 998 2171
Fax : +1 508 998 2391
cpb_usa@cpbourg.com

C.P.Bourg S.A.
Parc d'Affaire Silic
32, rue des Gémeaux - BP 60410
94573 Rungis - France
Tel. : +33 1 46 87 32 14
Fax : +33 1 46 87 52 17
Courriel: cpb_france@cpbourg.com

C.P.Bourg GmbH
Schweizerstrasse 70/1
D-72336 Balingen
Germany
Tel. : +49 7433 9981 680
Fax : +49 7433 9981 686
cpb_germany@cpbourg.com

C.P.Bourg S.A.
14 rue Millewee, B.P. 85
L-7201 Walferdange
Luxembourg
Tel. : +352 33 24 47
Fax : +352 33 19 99
cpb_luxembourg@cpbourg.com

BST_{10-d+}

Bourg Suction Tower
dual output
user-friendly touch screen

BOURG COLLATOR

 **c.p. bourg**



BOURG SUCTION TOWER dual output BST-d+

Less floor space, more flexibility!



C.P. BOURG has developed the BST10-d+ concept to give you total versatility within a Suction Tower System by allowing set transport to two different outputs, according to your finishing needs. The BST10-d+ is operated by a user-friendly touch screen console. It offers a great job diversity at the tip of your fingers.

The BST10-d+ collator enables you to utilize multiple finishing solutions within one single system. The need to change finishing attachments is now eliminated. SAVING TIME means better productivity.

The BST10-d+ concept is based on 3 different 10 bins towers: the main tower BST10-d+ right including touch screen, the main tower BST10-d+ left and the additional tower BST10-d+. This unique system is expandable with up to 3 additional towers for a maximum 50 bin capacity.

The Main towers BST10-d+ right / left may have their own touch screen and control the right / left side of the collator system, including the output to finishing accessories located on both side. The towers may send their sheets to the left or right side of the collator, based on operator selection made on touch screen. This results in VERY HIGH FLEXIBILITY of configuration.

The BST-d+ can be controlled by one single touch screen when the output is exclusively sent to the left or to the right.

The system can simultaneously produce:

- Via the right side output: saddle-stitched, folded and trimmed booklets using either the AGR-t/ PAS-t/ TR-t stitcher/folder/trimmer or the BDF Bourg Document Finisher combining all three functions in one self contained unit or SBM4.
- Via the left and/or right side output: straight stacked sets of NCR paper or separated sets for perfect binding at a later stage, for example. This can be done on a TD-t stacker or a criss-cross jogger. Because each side is controlled by its own touch screen, it allows two operators working simultaneously.

FEATURES →

■ Touch screen

The BST10-d+ is operated with a touch screen interface. All the functions of the collator are easy to reach. The operator does not have to bother with complicated programming of jobs.

■ High flexibility feeding device

All paper feeding parameters can be adjusted and fine tuned. This makes the BST10-d+ the most versatile collator available on the market today.

■ Dual output

Collated sheets can be delivered to both sides of the BST10-d+. It is possible to finish booklet on one side and receive sheets on a stacker or a jogger on the other side at the same time.

■ Load cover sheet while run

The two first trays can be loaded with the same sheets, usually the cover. When one tray is empty, the BST10-d+ automatically switches to the other one and the collation process never stops.

■ Load while run

The same job can be copied on the same tower or on the next tower. In case any tray empties, the collation process goes on automatically with the other part or the other tower. Trays can be reloaded while the collator runs.

■ Sheet between sets

Sometimes known as "insert function", a single sheet can be inserted between every certain number of sets. This process is optimised to safeguard the productivity of the machine.

■ Program saving and recall

A job can be saved in the memory of the BST10-d+ and recalled later. Programs are identified with names.

■ Complex collating jobs


This function allows collating complete sets. Several independent sequences can be executed in a row. To make a book with a cover, 90 NCR sheets, a reminder sheet, 10 NCR sheets and back cover is as simple as a standard job.

■ High productivity mode

When several towers are used, the productivity is maintained at its upper limit.

■ Marrying table

With an optional marrying table, a set can be manually completed.



TD-d + LH Exit Kit for BST-d+ + BST-d+ right + BDF



C/C mir. + BST-d+ left incl. touch screen + BST-d+ add. + BST-d+ right + SBM4



TD-d + BST-d+ left + BST-d+ add. + BST-d+ add. + BST-d+ right + TD-t



TD-d + BST-d+ left incl. touch screen + BST-d+ add. + BST-d+ add. + BST-d+ add. + BST-d+ right + AGR-t + PAS-t + TR-t